



• Product introduction - JS6128GHN

European city bus noble ancestry, simple lines, sharp but steady. It has advanced configuration, humanistic facilities, and high economic cost. The vehicle is strong and light, and can be equipped with Weichai engines, green environmental protection.



• JS6128GHN Product Configuration

基本参数 Overall specification	总长 Overall length(mm)	12000	发动机 Engine	发动机型号 Engine model	WP10NG300E51
	总宽 Overall width(mm)	2550		制造商 Manufacture	Weichai Power
	总高 Overall height(mm)	3450		位置 Engine position	Rear Engine
	轴距 Wheel base (mm)	5900		类型 Engine Type	CNG
	前后悬 F/R overhang(mm)	2650/3450		最大功率 Max power (km/hp)/rpm	200Kw/1900
	最大总质量 Max G.V.W(kg)	18000		最大扭矩 Max torque(N.M/rpm)	140N.m/1200-1500
	座位数/乘员数 Seats/Passenger qty	45+1/85		钢瓶容积 cylinder capacity (L)	640L
	最高车速 Max speed(km/h)	70		排放 Emission Standard	Euro5

**详细配置 Detailed configuration**

序号 Seq	项目 Item	标准 Standard
1	发动机 Engine	Weichai WP10NG300E51CNG
2	钢瓶容积 cylinder capacity (L)	80L*8 cylinders
3	变速箱 Gearbox	Local 5J150T manual gearbox with five speed 国产法士特 5J150T 五档手动变速箱
4	离合器 Clutch	430 Diagram spring clutch 膜片弹簧离合器
5	前桥 Front axle	front axle 国产 6.5T 德纳前桥
6	后桥 Rear axle	rear axle 国产 13T 德纳后桥
7	制动系统 Brake system	Pneumatic double circuit air brake, front disk and drum brake. 气压双回路制动, 前盘后鼓制动
8	悬挂 Suspension	Few leaf spring, with front and rear stabilizer bar 少片簧 (4/5), 带前后横向稳定杆
9	转向 Steering	Integral power steering 整体式动力转向
10	ABS	国产 ABS
11	自动调整臂 Automatic Slack Adjuster	Automatic Slack Adjuster 自动调整臂
12	缓速器 Retarder	Local electric retarder 国产电涡流缓速器
13	集中润滑 Centralized lubrication	无 No
14	冷却系统 Cooling system	Normal mechanic fan 普通机械风扇
15	轮胎 Tire	12R22.5 Tubeless tire without spare tire 无内胎子午线轮胎无备胎
16	轮罩 Wheel cover	No 无
17	风扇/空调 Fan/ A/C	Roof mounted 30000Kcal A/C 顶置 3 万大卡空调
18	暖风 Heater	NO
19	除霜 Defroster	Front windshield defroster 前风档自然风除霜器
20	乘客门 / 前门 Passenger door/front door	Pneumatic inward opening front and middle door, 前后气控气动内摆门 (2 扇)
21	地板 Floor	Glued bamboo floor covered local welding artificial leather 竹胶地板上铺国产可焊地板革
22	侧窗 Side window	下 1/3 固定, 上 2/3 推拉, 下固定部分采用粘结玻璃, 司机窗内藏式推拉窗, 灰玻 Lower 1/3 fixed window, upper 2/3 push window, The lower fixed part adopts bonded glass, and the driver's window is a hidden push-pull window, gray glass
23	乘客座椅 Passenger seat	41 张灰色公交座椅+350mm, 4 张折叠椅 41 grey citybus seats, 4 folded seats
24	驾驶员座椅 Driver's seat	Adjustable driver's high backrest seat 高靠背可调驾驶座椅



25	内饰 Interior	Standard inner trimming for A/C 标准空调内饰
26	车内照明 Interior lighting	Standard 标配
27	倒车镜 Rearview mirror	rod type rearview mirror(left short , right long) 杆式后视镜（左短右长）
28	顶天窗 Emergency exit	Roof exits without ventilator (2 units) 2 只顶部出口（不带换气扇）
29	电子钟 Clock	Digital clock 电子钟
30	遮阳帘 Sunshade	Half sun visor front windshield 半副前挡风遮阳
31	窗帘 Curtain	No
32	扶手和护栏 Handrails and guardrails	Spay-paint roll flower handrail/guardrails, 20 units of hand rings 喷塑辊花扶手杆、防护栏，20 个吊环
33	收放机 Cassette player	FM AM Radio 收放机
34	电视 TV	No
35	路牌 Road signs	Front & rear LED electric route indicator LED 前、后电子路牌
36	语音报站器 Voice announcer	No
37	投币机 Coin Machine	No
38	IC 卡机 IC card machine	No
39	监视器 Monitor	No
40	录像监控系统 Video surveillance system	Monitor (colorful), 320G hard disk storage, 4 Cameras 彩色倒车监视器（带车载监控系统，硬盘 320G），另配 4 个摄像头
41	机舱灭火装置 Fire Extinguisher	Three fire extinguisher in engine compartment 三只发动机仓自动灭火器
42	漆种 Paints	Imported painting 进口油漆
42	路况 Road conditions	Bad road condition 较坏路况
43	其他特殊要求 Other special requirements	1、 Hot area design for cooling system 热带地区加大散热设计 2、 two level steps flooring type, 二级踏步 3、 Driver Fan 司机风扇 4、 With wheelchair area and wheelchair guide board 带轮椅区和导板 5、 Cancel rear windshield 取消后挡风
44	续航里程 cruising mileage	6、 350KM 350 公里



- JS6128GHN Product Photos



